

CACI 2

5/24/2024

Engine RPM	IAC count	CLT (*F)	IAT (*F)	Speed (MPH)	Baro pressure- kPa	TPS volts	TPS %	MAF (gm/sec)	MAP (kPa)	Pressure Loss	MAP (volts)	BLM cell#	B1 O2 sensor- v	B2 O2 sensor- v	B1 LTFT BLM	B2 LTFT BLM	Spark adv degs	Knock retard degs	PE MODE	
3,668	84	172	87	45	97.81	3.39	87	158.68	93.75	4.06	-4.2%	4.43	15	0.888	0.892	147	148	32	0.0	1
4,012	84	172	87	48	97.81	3.75	98	168.99	93.38	4.43	-4.5%	4.41	15	0.901	0.884	147	148	33	0.0	1
4,213	84	172	87	51	97.81	3.76	98	183.62	93.75	4.06	-4.2%	4.43	15	0.892	0.884	147	148	36	0.0	1
4,652	84	172	87	56	97.81	3.94	100	203.11	91.90	5.91	-6.0%	4.33	15	0.897	0.884	147	148	36	0.0	1
4,608	84	172	87	57	97.81	3.82	100	200.19	92.64	5.17	-5.3%	4.37	15	0.892	0.884	147	148	36	0.0	1
4,835	84	172	87	59	97.81	3.88	100	216.80	93.38	4.43	-4.5%	4.41	15	0.892	0.884	147	148	36	0.0	1
5,024	84	172	86	61	97.81	3.90	100	208.58	93.01	4.80	-4.9%	4.39	15	0.901	0.892	147	148	36	0.0	1
5,192	84	172	86	64	97.81	3.90	100	215.29	90.80	7.01	-7.2%	4.27	15	0.901	0.892	147	148	36	0.0	1
5,362	84	172	86	66	97.81	3.88	100	215.29	91.17	6.64	-6.8%	4.29	15	0.901	0.888	147	148	37	0.0	1
5,441	84	172	86	67	97.81	3.88	100	221.11	90.06	7.75	-7.9%	4.24	15	0.906	0.888	147	148	37	0.0	1
5,482	84	172	86	69	97.81	3.88	100	226.75	89.32	8.49	-8.7%	4.20	15	0.901	0.888	147	148	37	0.0	1
5,771	84	172	86	71	97.81	3.90	100	233.63	89.69	8.12	-8.3%	4.22	15	0.897	0.888	147	148	37	0.0	1
5,875	84	173	86	72	97.81	3.90	100	217.18	91.90	5.91	-6.0%	4.33	15	0.888	0.888	147	148	37	0.0	1
6,006	84	173	86	74	97.81	3.84	100	229.35	91.54	6.27	-6.4%	4.31	15	0.884	0.875	147	148	37	0.0	1
5,946	84	173	86	74	97.81	0.78	4	45.16	26.59	71.22	-72.8%	0.86	3	0.915	0.919	143	143	41	0.0	1

Engine RPM	IAC count	CLT (*F)	IAT (*F)	Speed (MPH)	Baro pressure- kPa	TPS volts	TPS %	MAF (gm/sec)	MAP (kPa)	Pressure Loss	MAP (volts)	BLM cell#	B1 O2 sensor- v	B2 O2 sensor- v	B1 LTFT BLM	B2 LTFT BLM	Spark adv degs	Knock retard degs	PE MODE	
4,811	80	176	86	58	97.07	4.20	100	206.10	92.27	4.80	-4.9%	4.35	15	0.875	0.875	147	148	36	0.00	1
4,907	80	176	86	61	97.07	4.14	100	207.27	90.43	6.64	-6.8%	4.25	15	0.875	0.884	147	148	36	0.00	1
5,183	80	176	86	63	97.07	4.14	100	213.48	92.27	4.80	-4.9%	4.35	15	0.879	0.870	147	148	36	0.00	1
5,285	80	176	86	65	97.07	4.14	100	200.12	89.69	7.38	-7.6%	4.22	15	0.875	0.870	147	148	37	0.00	1
5,512	80	176	86	68	97.07	4.14	100	230.72	90.43	6.64	-6.8%	4.25	15	0.879	0.870	147	148	37	0.00	1
5,828	80	176	86	70	97.07	4.14	100	221.11	89.69	7.38	-7.6%	4.22	15	0.884	0.866	147	148	37	0.00	1
5,886	80	176	86	72	97.07	4.14	100	233.63	90.43	6.64	-6.8%	4.25	15	0.875	0.866	147	148	37	0.00	1
6,093	80	176	86	74	97.07	4.14	100	226.75	88.95	8.12	-8.4%	4.18	15	0.857	0.870	147	148	37	0.00	1
6,183	80	177	86	74	97.07	1.29	20	167.55	47.99	49.08	-50.6%	2.00	7	0.915	0.910	144	145	42	0.0	1